




City of Alameda

Alameda Fire Department Inspection Guidelines



ACCESS

- ☐ Fire apparatus access roads shall be unobstructed
- ☐ Access approval shall be provided for all fire protection equipment
- ☐ Knox Box required for gated community

ELECTRICAL

- ☐ Extension cords shall not be used as permanent wiring
- ☐ Extension cords shall be maintained in good condition

EXITS

- ☐ Provide lighting for corridors, stairways, exterior stairways
- ☐ All exit signs shall be illuminated at all times
- ☐ Fire escape stairs shall comply with this section
- ☐ Exits, and access to exits, maintained clear of obstruction

FIRE EXTINGUISHERS

- ☐ Provide extinguishers of the required rating
- ☐ Mount extinguishers not higher than 5 feet
- ☐ Post signs where extinguisher are not readily visible
- ☐ Service and tag extinguishers annually by state licensee company
- ☐ Provide protection for outside mounted extinguishers
- ☐ Fire extinguisher mounted within 75ft from the furthest point of living space

FIRE PROTECTION SYSTEMS

- ☐ Maintain access to standpipes, hose and valves
- ☐ Test sprinkler system quarterly and maintain records
- ☐ Service and have certified sprinklers and standpipes every 5 years

OUTSIDE RUBBISH

- ☐ Remove weeds and overgrowth
- ☐ Clear accumulation of combustible waste material
- ☐ Do not store or place within 5ft of building dumpsters and containers with a capacity of 1.5 cubic yards or more

STORAGE

- ☐ Storage of combustibles in building shall be orderly
- ☐ Keep exits and exit enclosures clear
- ☐ Storage in attic, under floor and concealed spaces shall be protected on storage side as required for 1hr fire-resistance-rated construction

PREMISE IDENTIFICATION

- ☐ Address or building or unit numbers are required and placed in a position legible and visible from the street